

RB-2021HEAVY DUTY GRINDER

Standard Specification:

1) Spindle Diameter and Thread - M 16 x 5/8" 2Wheel width: Min. 12mm & Max. 25 mm Air consumption on load 1.67 at 6.33 kg /cm3 Air Inlet Connection 1/2" BSP

Note:

Tools are supplied with guard but mounted point Grinding wheel is not in the standard scope of supply.

Specification:

Wheel Capacity Elastic Bonded Wire Brush Buffing Wheel r.p.m Length With Guard 150 x 25 mm 100 mm 150 mm 6000 578 mm 5.5 kg 6 x 1 in. 4 in. 6 in. 6 in. 12. 1/4 lb	150 x 25 mm	150 x 25 mm	Wheel Capacity			Free Speed	Overall	Appox	
6000	6000	6000	Wheel Capacity Elastic Bonded	Wire Brush	Buffing Wheel	r.p.m	Length	with Guard	
6 x 1 in. 4 in. 6 in. 22.3/4 in. 12.1/4 lb	6 x 1 in. 4 in. 6 in. 22.3/4 in. 12.1/4 lb	6 x 1 in. 4 in. 6 in. 22.3/4 in. 12.1/4 lb	150 x 25 mm	100 mm	150 mm	0000	578 mm	5.5 kg	
			6 x 1 in.	4 in.	6 in.	6000	22.3/4 in.	12. 1/4 lb	Į,
	7								
			7						